


# PBU



## DESCRIPTION:

The "PBU" utility panel with ribs 6" on centers is especially useful for liners, partitions, soffits, etc., because of its shallower 3/4" deep ribs and relative ease of erection.

### FEATURES:

- Galvalume®
- Reverse rolled profile
- Fire rating
- Continuous eave to sill until panel exceeds 40' length
- Signature® 300 Series Options
- Face fastener
- Embossed texture (optional)
- Bearing leg (optional)
- Perforated condition (optional)

### BENEFITS:

- 20 year warranty
- Places color on the reverse side of the panel yields a flat profile appearance with fasteners recessed in flutes
- Panel carries a UL "Class A" fire rating
- Attractive with no end laps, and ease of erection
- Premium paint finish with a 25 year warranty, ultimate resistance to color changes and chalk
- Yields diaphragm capabilities and girt stability
- Embossing the metal reduces glare and the potential for oil-canning
- A bearing leg is available to guarantee side lap engagement
- Ventilation or acoustical applications

**GAUGE:** 24 and 26 (standard) with 22 and 29 available upon special request.

**LENGTH:** Maximum recommended 40'. Longer lengths available on special order.

**FASTENERS:** Various self drilling depending on applications

**FINISH:** Galvalume®

**USAGE:** Wall panel, liner panel, soffit panel, mansard panel face and back sheet

**NOTE:** Oil-canning is not considered grounds for rejection of any panel system. Oil-canning can occur in any panel with wide flat sections. Heavier gauge, embossing, striations, flatter sub-frame systems and support from a solid sub-deck can all help to minimize oil-canning.