


VistaShadow[®]



DESCRIPTION:

The VistaShadow[®] panel produces a decorative smooth shadow line wall creating a distinctive architectural effect with semi-concealed fasteners. Ribs are 1 1/8" deep and major corrugations spaced 12" on center. The net coverage of panel is 3'-0".

FEATURES:

- Semi-concealed fastener panel
- Striations
- Signature[®] 200 and 300 Series
- Continuous eave to sill until panel exceeds 40'-0 length
- Optional Embossed texture
- UL "Class A" fire rating

BENEFITS:

- Attractive architectural application
- Reduces oil canning, textured appearance
- Attractive with no end laps, and ease of erection
- Premium paint finish with 20 year warranty, ultimate resistance to color changes and chalk
- The VistaShadow[®] panel carries a UL "Class A" fire rating.

GAUGE: 26 and 24

LENGTH: Maximum recommended 45'. Longer lengths available on special order.

DIMENSIONS: 36" wide by 1 1/8" deep

FASTENERS: Various, depending on application

FINISH: Galvalume[®], Signature[®] 200 & 300 Series

USAGE: Wall panel, liner panel, soffit panel, mansard panel face and back sheet.

LIMITATIONS: Installation may be difficult with very thick insulation.

NOTE: Oil-canning is not considered grounds for rejection of any panel system. Oil-canning can occur in any panel with wide flat sections. Heavier gauge, embossing, striations, flatter sub-frame systems and support from a solid sub-deck can all help to minimize oil-canning.