



# VistaSheen<sup>®</sup>



## DESCRIPTION:

Since the new PBR panel has been introduced to replace the VistaSheen<sup>®</sup> panel, it is used exclusively for additions to existing buildings containing VistaSheen<sup>®</sup>.

### FEATURES:

- 36" Coverage
- Trimless Ridge
- Start installation at either end
- Economical profile
- Finish Warranty
- Diaphragm Action
- Reverse Rolled Profile
- Purlin Bearing Leg

### BENEFITS:

- The panel qualifies under several UL90 construction numbers

**GAUGE:** 26 (standard), with 24 and 22 gauge optional

**LENGTH:** 45' maximum length is standard but longer lengths are available by special request.

**DIMENSIONS:** 36" coverage x 1 1/4"

**FASTENERS:** Standard coated, zinc- aluminum cast head, or stainless steel head screw.

**FINISH:** Galvalume<sup>®</sup>, Signature<sup>®</sup> 200 & 300 Series

**USAGE:** Roof & wall applications.

**LIMITATIONS:** Not designed for coverage over bar joist or to be used as rigid secondary. Five foot on center purlin spacing.

**NOTE:** Oil-canning is not considered grounds for rejection of any panel system. Oil-canning can occur in any panel with wide flat sections. Heavier gauge, embossing, striations, flatter sub-frame systems and support from a solid sub-deck can all help to minimize oil-canning.